

PRODUCT INDEX



 elica
aria nuova

**Register your product at elica.com
and get 1 extra year of warranty.**




3 YEARS

PARTS AND LABOR FULL WARRANTY

2+1 extra year when you register your product at elica.com
Applies for all Elica products. For U.S & Canada users only.
For valid warranty extension, register within 3 months from purchase.

 **elica**
aria nuova





—| ELICA INDEX v. 2023

			
Model Name	Trento Elica Pro Series	Arezzo Elica Pro Series	Scanno Elica Pro Series
Model Numbers	ETR628SS ETR634SS ETR134S1 ETR146SS	EAR628S4 EAR134S4 EAR634SS EAR140S4 EAR146S4	ESC628SS ESC134SS ESC146SS
Dimensions	28 1/2" W x 18" D x 11 7/8" H 34 1/2" W x 18" D x 11 1/2" H 46 1/2" W x 18" D x 11 1/2" H	28 1/2" W x 22" D x 11 7/8" H 34 1/2" W x 22" D x 11 7/8" H 40 1/2" W x 22" D x 11 7/8" H 46 1/2" W x 22" D x 11 7/8" H	28 1/2" W x 15 5/8" D x 11 15/16" H 34 1/2" W x 15 5/8" D x 11 15/16" H 46 1/2" W x 15 5/8" D x 11 15/16" H
Blower Type	600 CFM (4-speed) (28", 34") 1200 CFM (4-speed) (34", 46")	600 CFM (4-speed) (28", 34") 1200 CFM (4-speed) (34", 40" & 46")	600 CFM (3-speed) (28") 1200 CFM (3-speed) (28", 34")
CFM Reduction	No	No	Yes
Noise (sones)	7 sones (28", 34") 8.5 sones (34", 46")	7 sones (28", 34") 8.5 sones (34", 40", 46")	7 sones (28") 8.5 sones (34", 46")
Finish	Stainless Steel	Stainless Steel	Stainless Steel
Controls	Fully Retractable Rotating Knobs w/ Blue Backlighting	Fully Retractable Rotating Knobs w/ Blue Backlighting	Fully Retractable Rotating Knobs w/ Blue Backlighting
Illumination	2 LED, 6.5 W, 3000K <small>*Consumer Replaceable</small>	2 LED, 7.5 W, 3000K (28", 34") 4 LED, 7.5 W, 3000K (40", 46") <small>*Consumer Replaceable</small>	2 LED, 7.5 W 3000K (28") 4 LED, 7.5 W 3000K (34", 46") <small>*Consumer Replaceable</small>
Filter Type	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter	Dishwasher-Safe, Professional Stainless Steel Baffle Filters <small>for 28", 34" & 3 for 46"</small>
Duct Transition	10" Round with Backdraft Damper (top only)	10" Round with Backdraft Damper (top only)	10" Round with Backdraft Damper (top only)
Installation Type	Ducted or Recirculating with kit	Ducted or Recirculating with kit	Ducted or Recirculating with kit
Electrical	120 V - 60 Hz, 490 W (28", 34") 120 V - 60 Hz, 913 W (34") 120 V - 60 Hz, 926 W (46")	120 V - 60 Hz, 463 W (28") 120 V - 60 Hz, 490 W (34") 120 V - 60 Hz, 913 W (34") 120 V - 60 Hz, 926 W (46")	120V - 60 Hz, 490 W (28", 34") 120V - 60 Hz, 913 W (46")
Kits Available	KIT0153054 - (External blower) KIT0154387 - (Inline blower) Recirculating Kit KIT0192763 - (Deflector) KIT0192765 - (Round carbon filters)	KIT0153054 - (External blower) KIT0154387 - (Inline blower) Recirculating Kit KIT0192763 - (Deflector) KIT0192765 - (Round carbon filters)	KIT0153054 - (1200 CFM External Blower Kit) KIT0154387 - (1200 CFM Inline Blower Kit) KIT0179549 - (Inline Blower Shell Kit) KIT0179547 - (External Blower Shell Kit) KIT0185752 - (CFM Reduction Kit) Recirculating Kit KIT0192763 - (Deflector) KIT0192765 - (Round carbon filters)

SPECS

Inserts






				
Model Name	Palermo Techne Series	Umbria Techne Series	Asti Comfort Series	Asti 30" Comfort Series
Model Numbers	EPR628S1 EPR634SS	EUM628SS EUM634SS	EAS422SS EAS428S1	EAS430SS
Dimensions	28 1/4" W x 10 3/4" D x 9 1/2" H 34 1/5" W x 10 3/4" D x 9 1/2" H	28 1/4" W x 10 3/4" D x 10 11/16" H 34 1/4" W x 10 3/4" D x 10 11/16" H	22 1/2" W x 10 3/4" D x 9 1/2" H 28 1/4" W x 10 3/4" D x 9 1/2" H	30" W x 12" D x 5/8" H
Blower Type	600 CFM (3-speed)	600 CFM (3-speed)	400 CFM (3-speed)	400 CFM (3-speed)
CFM Reduction	Yes	Yes	Yes	Yes
Noise (sones)	6.8 sones	6.8 sones	5.9 sones	4 sones
Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Controls	Stainless Steel Push Buttons	Stainless Steel Push Buttons	Backlit Electronic Push Buttons	Mechanical Push Buttons
Illumination	2 LED, 2.5 W, 4000K	2 LED, 2.1 W, 4000K	2 LED, 2.1 W 4000K	2 LED, 6.5 W, 3000K
Filter Type	Dishwasher-Safe, Professional Stainless Steel Baffle Filters	Dishwasher-Safe, Anodized Aluminum, Mesh Filter + Perimeter Aspiration	Dishwasher-Safe, Anodized Aluminum Mesh	Aluminum Mesh + Stainless Steel Layer
Duct Transition	6" Round with Backdraft Damper (top only)	6" Round with Backdraft Damper (top only)	6" Round with Backdraft Damper (top only)	6" Round with Backdraft Damper (top only)
Installation Type	Ducted or Recirculating w/kit	Ducted or Recirculating w/kit	Ducted or Recirculating w/kit	Ducted or Recirculating w/kit
Electrical	120 V - 60 Hz, 289 W	20V-60Hz, 455 W	120 V - 60 Hz, 289 W	120 V - 60 Hz, 260 W
Kits Available	KITO2773 - (30" liner) KITO2774 - (36" liner) KITO2770 - (Recirculating Kit) KITO2748 - (CFM Reduction Kit)	KITO2770 - (Recirculating Kit) KITO2773 (28") - (30" Hood Liner) KITO2774 (28") - (36" Hood Liner) KITO175561 - (Electronic CFM Reduction Bypass Kit)	KITO175561 - (CFM Reduction) KITO2770 - (Recirculating Kit) KITO2773 - (30" liner) KITO2774 - (36" liner) KITO175561 - (CFM Reduction Kit)	KITO175561 - (CFM Reduction) KITO2773 - (30" liner) KITO2770 - (Recirculating Kit)

SPECS

Undercabinet







			
Model Name	Cervinia Elica Pro Series	Calabria Elica Pro Series	Modena Techne Series
Model Numbers	ECV630S3 ECV636S3	ECL630S4 ECL636SS ECL136S4 ECL142S4 ECL148S4	EMD530S3 EMD536S3
Dimensions	30"W x 23"D x 11 1/32"H 36"W x 23"D x 11 1/32"H	30"W x 25"D x 18"H 36"W x 25"D x 18"H 42"W x 25"D x 18"H 48"W x 25"D x 18"H	30" W x 19 5/8"D x 9 3/4" H 36" W x 19 5/8"D x 9 3/4" H
Blower Type	600 CFM (4-speed)	600 CFM (3-speed + boost) (30", 36") 1200 CFM (3-speed + boost) (36", 42", 48")	600 CFM (3-speed + boost)
CFM Reduction	Yes	Yes	Yes w/ Kit
Noise (sones)	7 sones	7 sones (30", 36") 8.5 sones (36", 42", 48")	6.8 sones
Finish	Stainless Steel	Stainless Steel	Stainless Steel + Black Tempered glass
Controls	Fully Retractable Rotating Knobs w/ Blue Backlighting	Fully Retractable Rotating Knobs w/ Blue Backlighting	Capacitive Touch (Glass)
Illumination	2 LED, 6.5 W, 3000K	2 LED, 6.5 W, 3000K (30",36",42") 4 LED, 6.5 W, 3000K (48")	2 Premium LED Dimmable, 2.1 W, 4000K
Filter Type	Dishwasher-Safe, Professional Stainless Steel Baffle Filter	Dishwasher-Safe, Professional Stainless Steel Baffle Filter	Dishwasher-Safe, Stainless Steel Microhole Filter
Duct Transition	3 1/4" x 10" with Backdraft Damper (Top or Rear)	3 1/4" x 10" with Backdraft Damper (Top or Rear)	3 1/4" x 10" (Rear outlet) or 6" Round (Top outlet)
Installation Type	Ducted Installation Only	Ducted Installation Only	Ducted or Recirculating w/kit
Electrical	120 V - 60 Hz, 457 W	120 V - 60 Hz, 463 W 120 V - 60 Hz, 490 W 120 V - 60 Hz, 913 W 120 V - 60 Hz, 926 W	120 V - 60 Hz, 445 W
Kits Available	KITO2159-KITO2158 - (Chimney extension 6") KITO2160-KITO2161 - (Chimney extension 12") KITO142864 - KITO142867- (Back Splash Kit) KITO154387 for 1200 CFM - (Inline Blower Kit) KITO153054 for 1200 CFM - (External Blower Kit) KITO185097- (CFM Reduction Kit)	KT02159 - KITO2158 - KIT2622 -KIT2164 (Chimney extension 6") KITO2160-KITO2161-KIT2623-KIT2165 (Chimney extension 12") KITO155106-KITO155107-KITO155110- KITO155111 - (Heat Lamp Kit) KITO142864- KITO142867- KITO142868- KITO142870 - (Stainless steel Backsplash) KITO153054 - (1200 CFM External blower) KITO154387 - (1200 CFM Inline blower) KITO179549 - (Inline Blower Shell Kit) KITO179547 - (External Blower Shell Kit) KITO185752 - KITO185099 - (CFM Reduction Kit) Recirculating Kit KITO192763 - (Deflector) KITO192765 - (Round carbon filters)	KITO2667 - (Recirculating Kit)

SPECS

Undercabinet







				
Model Name	Aria Techne Series	Bellagio Comfort Series	Nemi Comfort Series	Fusaro Comfort Series
Model Numbers	EAI430SS EAI436SS	EBL430S1 EBL430W1 EBL436S1	ENM230S1 ENM236S1 ENM230W1 ENM230B1	EFS130S1
Dimensions	30"W x 20"D x 4 7/10" H 36"W x 20"D x 4 7/10" H	30" W x 20"D x 4 1/2" H 36" W x 20"D x 4 1/2" H	30" W x 18 5/8" D x 5" H 36"W x 18 5/8" D x 5" H	30" W x 18 5/8" D x 5" H
Blower Type	430 CFM (3-speed + boost)	430 CFM (3-speed + boost)	280 CFM (3-speed)	190 CFM(2-speed)
CFM Reduction	Yes w/Kit	Yes w/ Kit	No	No
Noise (sones)	6.1 sones	6.1 sones	4.9 sones	4.1 sones
Finish	Stainless Steel + Black Tempered glass	Stainless Steel	Stainless Steel, Black & White	Stainless Steel
Controls	Capacitive Touch (Glass)	Multi-function Electronic with LCD Display	Backlit Electronic Push Buttons	Rocker Switches
Illumination	2 Premium LED Dimmable, 2.1 W, 4000K	2 LED, 6.5 W, 3000K	2 LED, 2.1 W, 4000 K	1.75 W Incandescent lamp, 1 intensity
Filter Type	Dishwasher-Safe, Stainless Steel Baffle Slot Filter	Dishwasher-Safe, Anodized Aluminum Mesh	Dishwasher-Safe, Anodized Aluminum Mesh	Dishwasher-Safe, Anodized Aluminum Mesh
Duct Transition	3 1/4" x 10" (Top or Rear) or 7" Round (sold separately)	3 1/4" x 10" (Top or Rear) or 7" Round (sold separately)	3 1/4" x 10" (Top or Rear) or 7" Round (sold separately)	3 1/4" x 10" (Top or Rear) or 7" Round (sold separately)
Installation Type	Ducted or Recirculating w/kit	Ducted or Recirculating w/kit	Ducted or Recirculating w/kit	Ducted or Recirculating w/kit
Electrical	120 V - 60 Hz, 333 W	120 V - 60 Hz, 445 W	120 V - 60 Hz, 115 W	120 V - 60 Hz, 110 W
Kits Available	KIT02723 - (7" Back Draft) KIT02178 - (CFM Recution for 30") KIT02179 - (CFM Recution for 36")	KIT02723 - (No return valve) KIT02178 - (CFM Reduction Kit for 30") KIT02179 - (CFM Recution Kit for 36")	KIT02722 - (7" duct transition) KIT02723 - (No return valve 7") KIT0140997 - (Recirculating Kit)	KIT02722 - (Duct transition, 7" round transition) KIT02723 - (7" Backdraft Damper) KIT02724 - (No return valve - 10" x 3 1/4" rectangular)

SPECS

Undercabinet



				
Model Name	Allasio Comfort Series	Sora Comfort Series	Gubbio Comfort Series	TT Comfort Series
Model Numbers	EAL330S1 EAL336S1 EAL330W1 EAL330B1	ESR430S1 ESR436S1	EGB224SS	ETT424S1 ETT430SS ETT436SS
Dimensions	30"W x 20"D x 4 ³ / ₄ "H 36"W x 20"D x 4 ³ / ₄ "H	30"W x 23"D x 10"H 36"W x 23"D x 10"H	24"W x 18 ⁷ / ₈ "D x 4 ¹⁵ / ₁₆ "H	24"W x 11-17"D x 11 ³ / ₄ "H 30"W x 11-17"D x 11 ³ / ₄ "H 36"W x 11-17"D x 11 ³ / ₄ "H
Blower Type	300 CFM (3-speed)	400 CFM (2-speed)	250 CFM (3-speed)	400 CFM (3-speed)
CFM Reduction	No	Yes w/Kit	No	Yes w/Kit
Noise (sones)	5.2 sones	5.9 sones	4.6 Sones	5.9 Sones
Finish	Stainless Steel Black White	Stainless Steel	Stainless Steel	Stainless Steel
Controls	Backlit Electronic Push Buttons	Rocker Switches	Mechanical Slider Control	Hidden Electronic Touch Controls
Illumination	2 LED, 2.1 W, 3000K	2 LED, 2.1 W 4000K	2 LED , 2.1 W, 3000K	2 LED, 2.1 W, 3000K
Filter Type	Dishwasher-Safe, Anodized Aluminum Mesh	Dishwasher-Safe, Stainless Steel Baffle Slot Filter	Dishwasher-Safe, Anodized Aluminum Mesh	Dishwasher-Safe, Anodized Aluminum Mesh
Duct Transition	3 ¹ / ₄ " x 10" with Backdraft Damper (Top or Rear)	3 ¹ / ₄ " x 10" with Backdraft Damper (Top or Rear)	3 ¹ / ₄ " x 10" with Backdraft Damper (Top or Rear)	6" Round Top Discharge
Installation Type	Ducted or Recirculating w/kit	Ducted or Recirculating w/kit	Ducted or Recirculating w/kit	Ducted or Recirculating w/kit
Electrical	120 V - 60 Hz, 289 W	120 V - 60 Hz, 265 W	120 V - 60 Hz, 115 W	120 V - 60 Hz, 245 W
Kits Available	KITO2723 - (No return valve 7") KITO2178 - KITO2179 - (Recirculating Kit) GRI0131086A - GRI0131087A (Upgrade Filter Kit)	KITO2770 - (Recirculating kit) KITO185097 - (CFM Reduction Kit)	KITO2722 - (7" duct transition) KITO2723 - (No return valve 7") KITO140997- (Recirculating kit)	CFC0038668 - (Charcoal Filter kit) DF01EA - (Recirculating Kit) KITO2748 - (CFM Reduction Kit)

SPECS

Undercabinet - Wall Mount Chimney Hoods







Model Name	Leone Elica Pro Series	Vavano Elica Pro Series	Lugano Techne Series
Model Numbers	ELN630S2 ELN636SS ELN136S2 ELN142S2 ELN148SS	EVV636S1 EVV648S1	ELG630S3 ELG636S3
Dimensions	30"W x 24"D x 12 1/8"H 36"W x 24"D x 12 1/8"H 42"W x 24"D x 12 1/8"H 48"W x 24"D x 12 1/8"H	36"W x 24"D x 30" - 54" H 48"W x 24"D x 30" - 54" H	30" W x 19 7/8" D x 23 15/16" H 36" W x 19 7/8" D x 23 15/16" H
Blower Type	600 CFM (4-speed) (30", 36") 1200 CFM (4-speed) (36", 42", 48")	600 CFM (4-speed)	600 CFM (3-speed + boost)
CFM Reduction	Yes w/ Kit	Yes w/ Kit	No
Noise (sones)	7 sones (30", 36") 8.5 sones (36", 42", 48")	7 sones	6.8 sones
Finish	Stainless Steel	Stainless Steel	Stainless Steel + Black Tempered Glass
Controls	Fully Retractable Rotating Knobs w/ Blue Backlighting	Fully Retractable Rotating Knobs w/ Blue Backlight	Capacitive Touch (Glass)
Illumination	2 LED, 6.5 W, 3000K <small>*Consumer replaceable</small>	2 LED, 6.5 W, 3000K <small>*Consumer replaceable</small>	2 Premium Dimmable LED 2.1 W, 4000K
Filter Type	Dishwasher-Safe, Professional Stainless Steel Baffle Filters <small>(2w/ 30", 36", 42" & 3w/48")</small>	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filters <small>(2w/ 36" & 3w/48")</small>	Dishwasher-Safe, Anodized Aluminum, Mesh Filter + Perimeter Aspiration
Duct Transition	8" Round with Backdraft Damper (Top Only)	8" Round with Backdraft Damper (Top Only)	6" Round with Backdraft Damper (Top Only)
Duct Cover Width	13 1/8"	13 5/64"	13"
Installation Type	Ducted or Recirculating with kit	Ducted Installation only	Ducted or Recirculating w/kit
Electrical	120 V - 60 Hz, 463 W 120 V - 60 Hz, 490 W 120 V - 60 Hz, 913 W	120 V - 60 Hz 490 W	120 V - 60 Hz, 450 W 120 V - 60 Hz, 495 W
Kits Available	KIT02785 - (Long Chimney Extension 13") KIT0153054 - (1200 CFM External Blower) KIT0154387 - (1200 CFM In Line Blower) KIT0179549 - (Inline Blower Shell Kit) KIT0179547 - (External Blower Shell Kit) KIT0185752 -KIT0185099 (CFM Reduction Kit) Recirculating Kit KIT0192759 - (Deflector) KIT0192765 - (Round carbon filters)	KIT0154387 - (1200 CFM Inline blower) KIT0153054 - (1200 CFM External blower) KIT0146881-KIT02785 - (Long Chimney Extension 13' 6") KIT0185752 - (CFM Reduction Kit) BH01UB - (6" Round Transition Kit)	KIT02785-KIT01935 - (Long Chimney Extension) KIT0141918 - (Charcoal filter) KIT0141925 - (Recirculating Kit)

SPECS

Wall Mount Chimney Hoods







				
Model Name	Foglia Techne Series	Como Techne Series	Varna Techne Series	Mezzano Techne Series
Model Numbers	EFG630S1 EFG636S1	ECM630S3 ECM636S3	EVR630S2 EVR636S2	EMZ630S3 EMZ636S3
Dimensions	30"W x 19 11/16"D x 28 5/16" - 42 1/8"H 36"W x 19 11/16"D x 28 5/16" - 42 1/8"H	30"W x 19 11/16"D x 29 11/16" - 54 1/6"H 36"W x 19 11/16"D x 29 11/16" - 54 1/6"H	30"W x 19 11/16"D x 28 3/8" - 42 1/8"H 36"W x 19 11/16"D x 28 3/8" - 42 1/8"H	30"W x 19 11/16"D x 29 11/16" - 54 11/64"H 36"W x 19 11/16"D x 29 11/16" - 54 11/64"H
Blower Type	600 CFM (3-speed + boost)	600 CFM (3-speed + boost)	600 CFM (3-speed + boost)	600 CFM (3-speed + boost)
CFM Reduction	No	Yes	No	No
Noise (sones)	6.8 sonos	6.8 sonos	6.8 sonos	6.8 sonos
Finish	Stainless Steel + Black Tempered Glass	Stainless Steel + Black Tempered Glass	Stainless Steel + Black Tempered Glass	Stainless Steel + Black Tempered Glass
Controls	Capacitive Touch (Glass)	Capacitive Touch (Glass)	Capacitive Touch (Glass)	Capacitive Touch (Glass)
Illumination	Premium Dimmable LED 2.1 W, 4000K	Premium LED Dimmable 2.1 W, 4000K	Premium LED Dimmable, 2.1 W, 4000K	Premium Dimmable LED 2.1 W, 4000K
Filter Type	Dishwasher-Safe, Stainless Steel Microhole Filter	Dishwasher-Safe, Stainless Steel Microhole Filter	Dishwasher-Safe, Stainless Steel Microhole Filter	Dishwasher-Safe, Stainless Steel Microhole Filter
Duct Transition	6" Round with Backdraft Damper (Top Only)	6" Round with Backdraft Damper (Top Only)	6" Round Top Discharge	6" Round with Backdraft Damper (Top Only)
Duct Cover Width	8 3/16"	13"	8 3/16"	13"
Installation Type	Ducted or Recirculating w/kit	Ducted Installation Only	Ducted or Recirculating w/kit	Ducted or Recirculating w/kit
Electrical	120 V - 60 Hz, 455 W	120 V - 60 Hz, 395 W	120 V - 60 Hz, 455 W	120 V - 60 Hz, 455 W
Kits Available	KIT02784 - (Long Chimney Extension) KIT02766 - (Recirculating Kit)	KIT02667 - (Charcoal filter) KIT0100315 - (Long Chimney Extension) KIT02766 - (Recirculating Kit)	KIT02766 - (Recirculating Kit) KIT02762 - (Long Chimney Extension)	KIT0102875 - (Recirculating Kit) KIT02785 - (Long Chimney Extension)

SPECS

Wall Mount Chimney Hoods









				
Model Name	Toblino 24" Comfort Series	Toblino Comfort Series	Volterra Comfort Series	Potenza Comfort Series
Model Numbers	ETB424SS	ETB430S3 ETB436S3	EVL424SS EVL430S2 EVL436S2	EPT430S3 EPT436S3
Dimensions	24" W x 19 11/16" D x 21 1/2" - 35" H	30" W x 19 11/16" D x 20 1/2" H 36" W x 19 11/16" D x 20 1/2" H	23 5/8" W x 19 11/16" D x 28 3/8" - 41 1/8" H 30" W x 19 11/16" D x 28 3/8" - 41 1/8" H 36" W x 19 11/16" D x 28 3/8" - 41 1/8" H	30" W x 19 11/16" D x 20 3/8" - 36 5/8" H 36" W x 19 11/16" D x 20 3/8" - 36 5/8" H
Blower Type	400 CFM (3-speed)	400 CFM (4-speed)	400 CFM (3-speed)	400 CFM (4-speed)
CFM Reduction	Yes w/ Kit	Yes w/ Kit	Yes w/ Kit	Yes
Noise (sones)	5.9 sones	5.9 sones	5.9 sones	5.9 sones
Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Controls	Backlit Electronic Push Buttons	Electronic Touch Controls with Adjustable Color Backlight	Backlit Electronic Push Buttons	Multiple Backlight Color Touch Controls
Illumination	2 LED Lights, 2.1 W, 4000K	2 LED, 2.1 W, 3000K	2 LED, 2.1 W, 4000K	2 LED, 2.1 W, 3000K
Filter Type	Dishwasher-Safe, Anodized Aluminum Mesh Filter	Dishwasher-Safe, Anodized Aluminum Mesh Filter <small>(2w/ 30" & 3w/36")</small>	Dishwasher-Safe, Anodized Aluminum Mesh Filter <small>(2w/ 24" & 3 w/36",30")</small>	Dishwasher-Safe, Anodized Aluminum Mesh Filter
Duct Transition	6" Round with Backdraft Damper (Top Only)	6" Round with Backdraft Damper (Top only)	3 1/4" x 10" (Top or Rear) or 7" Round (Sold Separately)	6" Round with Back Draft Damper (Top Only)
Duct Cover Width	13"	13"	8 3/16"	13 1/32"
Installation Type	Ducted or Recirculating (Kit sold separately)	Ducted or Recirculating (Kit sold separately)	Ducted or Recirculating w/kit	Ducted or Recirculating w/kit
Electrical	120V - 60 Hz, 260 W	120V - 60 Hz, 265 W	120 V - 60 Hz, 265 W	120 V - 60 Hz, 301 W
Kits Available	KIT02785-KIT01935- (Long Chimney Extension) KIT0102875 - (Recirculating Kit) GFO4YB - (Upgrade Filter Kit) KIT0175561 - (CFM Reduction Kit)	KIT02785 - (Long Chimney Extension) KIT0102875 - KIT01935 - (Recirculating Kit) KIT0175561 - (CFM Reduction Kit)	KIT02762 - (Long Chimney Extension) KIT02766 - (Recirculating Kit) GFO4YB - (Upgrade Filter Kit) KIT0175561 - (CFM Reduction Kit)	KIT0102875 - (Recirculating Kit) KIT0100315- KIT01609/1 - (Long Chimney Extension) GFO4YB - (Upgrade Filter Kit)

SPECS

Wall Mount Chimney Hoods



			
Model Name	Bolsena Comfort Series	Haiku Wall 13\" Iconic Series	Haiku Wall Iconic Series
Model Numbers	EBS630SS EBS636SS	EHK613SS	EHK624SS EHK636SS EHK636WH EHK648SS EHK636BL
Dimensions	30\"W x 19 ¹¹ / ₁₆ \"D x 28 ³ / ₄ \"- 41 ¹ / ₈ \"H 36\"W x 19 ¹¹ / ₁₆ \"D x 28 ³ / ₄ \"- 41 ¹ / ₈ \"H	13\" W x 12 ³ / ₅ \" D x 32\"- 49\" H	24\" W x 12 ³ / ₅ \" D x 32\"- 49\" H 36\" W x 12 ³ / ₅ \" D x 32\"- 49\" H 48\" W x 12 ³ / ₅ \" D x 32\"- 49\" H
Blower Type	600 CFM (4-speed)	600 CFM (3 speed + Boost)	600 CFM (3 speed + Boost)
CFM Reduction	Yes w/ Kit	No	No
Noise (sones)	6.8 Sones	6.8 Sones	6.8 sones
Finish	Stainless Steel	Stainless Steel	Stainless Steel Black Glass White KRION®
Controls	Multiple Backlight Color Touch Controls	Sensitive Touch Control with Backlight	Sensitive Touch Control with Backlight
Illumination	2 LED, 2.1 W, 3000K	Strip LED light 7 W, 3500 K	Strip LED light 7 W, 3500 K
Filter Type	Dishwasher-Safe, Stainless Steel, Baffle Slot Filters <small>(2w/ 30\" & 3 w/36\")</small>	Sophisticated black iron grates + 6 layer mesh filter	Sophisticated black iron grates + 6 layer mesh filter
Duct Transition	3 ¹ / ₄ \" x 10\" (Top or Rear) or 7\" Round (sold separately)	6\" Round Top Discharge	6\" Round Top Discharge
Duct Cover Width	8 ³ / ₁₆ \"	12\"	12\"
Installation Type	Ducted or Recirculating w/kit	Ducted or recirculating w/kit	Ducted or recirculating w/ kit
Electrical	120 V - 60 Hz, 265 W	120 V - 60 Hz, 460 W	120 V - 60 Hz, 460 W
Kits Available	KIT02762 - (Long Chimney Extension) KIT02766 - (Recirculating Kit)	CFC0141725AUL - (Recirculating Kit)	CFC0141725AUL - (Recirculating Kit)




			
Model Name	Salice Techne Series	Leone Island Elica Pro Series	Vavano Island Elica Pro Series
Model Numbers	ESL636S3 ESL642S3	ELI136S2 ELI142S2	EVI642S1 EVI648S1
Dimensions	36" W x 27 ¹³ / ₁₆ " D x 32 ⁴ / ₅ " - 52 ⁴ / ₅ " H 42" W x 27 ¹³ / ₁₆ " D x 32 ⁴ / ₅ " - 52 ⁴ / ₅ " H	36" W x 27" D x 37 ¹ / ₂ " - 46 ⁹ / ₁₆ " H 42" W x 27" D x 37 ¹ / ₂ " - 46 ⁹ / ₁₆ " H	42" W x 24" D x 30" - 51" H 48" W x 24" D x 30" - 51" H
Blower Type	600 CFM (3-speed+boost)	1200 CFM (4-speed)	600 CFM (4-speed)
CFM Reduction	No	Yes w/ Kit	Yes w/ Kit
Noise (sones)	6.8 Sones	8.5 sones	7 sones
Finish	Stainless Steel + Black Tempered Glass	Stainless Steel	Stainless Steel
Controls	Capacitive Touch (Glass)	Fully Retractable Rotating Knobs w/ Blue Backlighting <small>*Consumer Replaceable</small>	Fully Retractable Rotating Knobs w/ Blue Backlighting <small>*Consumer Replaceable</small>
Illumination	Premium Dimmable LED Lights, 2.1 W, 4000K	4 LED, 6.5 W, 3000K	4 LED, 6.5 W, 3000K
Filter Type	Dishwasher-Safe, Anodized Aluminum Mesh filter + Perimeter Aspiration <small>(4w/ 36" & 42")</small>	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filters	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filters
Duct Transition	6" Round with Backdraft Damper (Top Only)	8" Round with Backdraft Damper (Top Only)	8" Round with Backdraft Damper (Top Only)
Duct Cover Width	13 ² / ₅ "	13 ¹ / ₈ "	13"
Installation Type	Ducted or Recirculating with kit	Ducted or Recirculating with kit	Ducted Installation Only
Electrical	120 V - 60 Hz, 540 W	120 V - 60 Hz, 926 W	120 V - 60 Hz, 480 W
Kits Available	KIT0141924 - (Recirculating Kit) KIT0100317 - (Long Chimney Extension) KIT0141918 - (Charcoal filter)	KIT0153054 - (External blower Kit) KIT0154387 - (Inline blower Kit) KIT0100317 - (Long Chimney Extension 13' 6") KIT0179549 - (Inline blower Shell Kit) KIT0179547 - (External blower Shell Kit) KIT0185099 - (CFM Reduction Kit) Recirculating Kit KIT0192761 - (Deflector) KIT0192765 - (Round Carbon Filters)	KIT0145610 - (Long Chimney Extension 12") KIT0154387 - (Inline blower Kit) KIT0153054 - (External blower Kit) KIT0185752 - (CFM Reduction Kit) BH01UB - (6" Round Transition Kit)



			
Model Name	Maggiore Techne Series	Cingoli Techne Series	Easy Iconic Series
Model Numbers	EMG636S1 EMG642S1	ECN636S3 ECN642S3	EES320SS EES320WT
Dimensions	36"W x 27 1/8"D x 29 13/16" - 50 1/8"H 42"W x 27 1/8"D x 29 13/16" - 50 1/8"H	36"W x 25 1/4"D x 29 13/32" - 49 13/32"H 42"W x 25 1/4"D x 29 13/32" - 49 13/32"H	20"W x 20"D x 21" - 51"H
Blower Type	600 CFM (3-speed+boost)	600 CFM (3-speed + boost)	355 CFM (3-speed + booster)
CFM Reduction	No	No	No
Noise (sones)	6.8 Sones	6.8 sones	6.8 Sones
Finish	Stainless Steel + Black Tempered Glass	Stainless Steel + Black Tempered Glass	Stainless Steel White
Controls	Capacitive Touch (Glass)	Capacitive Touch (Glass)	Electronic push with perimetral light
Illumination	Premium Dimmable LED 2.1 W, 4000K	Premium Dimmable LED 2.1 W 4000K	3 LED, 2.5 W, 4000K
Filter Type	Dishwasher-Safe, Stainless Steel Microhole Filter	Dishwasher-Safe, Stainless Steel Microhole Grease Filter	Dishwasher-Safe, Aluminum Mesh Filter + Perimeter Aspiration
Duct Transition	6" Round with Backdraft Damper (Top Only)	6" Round with Backdraft Damper (Top Only)	Not applicable
Duct Cover Width	13"	13"	Not applicable
Installation Type	Ducted or Recirculating w/kit	Ducted or Recirculating w/kit	Recirculating Installation Only
Electrical	120 V - 60 Hz, 426 W	120 V - 60 Hz, 394 W	120 V - 60 Hz, 460 W
Kits Available	KIT02665 - (Recirculating Kit) KIT0100317 - (Long Chimney Extension) KIT02667 - (Charcoal filter)	KIT02665 - (Recirculating Kit) KIT0100317 - (Long Chimney Extension) KIT02667 - (Charcoal Kit)	KIT0121394 - (Wallmounting Bracket Kit) KIT01921 - (High Ceiling Extension Kit)

SPECS

Island Hoods





			
Model Name	Seashell Iconic Series	Haiku Island 13\" Iconic Series	Haiku Island Iconic Series
Model Numbers	ESS432SS	EHI613SS	EHI648SS EHI648BL EHI648WH EHI670SS
Dimensions	31 1/2\" W x 22 13/32\" - 61 13/32\" H	13\" W x 13\" D x 33\"- 49\" H	48\" W x 13\" D x 33\"- 49\"H 70\" W x 13\" D x 33\"- 49\"H
Blower Type	400 CFM (4-speed)	600 CFM (3 speed + Boost)	600 CFM (3 speed + Boost)
CFM Reduction	No	No	No
Noise (sones)	5.9 Sones	6.8 Sones	6.8 sones
Finish	Mirror Stainless Steel	Stainless Steel	Stainless Steel Clear Black Glass White KRION®
Controls	3S+B Remote Control	Sensitive Touch Control with Backlight	Sensitive Touch Control with Backlight
Illumination	4 Strip LED + Led Disk, 3500K	Strip LED 1 x 7 W 3500 K	Strip LED 1 x 7 W 3500 K
Filter Type	Aluminium grease filter + Regenerable charcoal filter	Sophisticated black iron grates + 6 layer mesh filter	Sophisticated black iron grates + 6 layer mesh filter
Duct Transition	Not applicable	6\" Round Top Discharge	6\" Round Top Discharge
Duct Cover Width	Not applicable	12\"	12\"
Installation Type	Recirculating Installation Only	Ducted or recirculating w/kit	Ducted or recirculating w/kit
Electrical	120 V - 60 Hz	120 V - 60 Hz, 460 W	120 V - 60 Hz, 460 W
Kits Available	KIT0067590 - (Extension Cable) KIT0121469 - (Black remote control) KIT0121468 - (White remote control)	CFC0141725AUL - (Recirculating Kit)	CFC0141725AUL - (Recirculating Kit)

		
Model Name	Illusion Iconic Series	Hilight Iconic Series
Model Numbers	EIL640DW EIL640WH	EHL640SS EHL640WH
Dimensions	40" W x 19 ¹⁷ / ₂₅ " D	40" W x 22" D
Blower Type	600 CFM (3 speed + boost)	600 CFM (3 speed + boost)
CFM Reduction	No	No
Noise (sones)	6.8 Sones	6.8 sones
Finish	Naked Panel Ready (stainless steel) + Stainless Steel Frame Metal White with White Frame	Stainless Steel Panel with Stainless Steel frame White Glass with Metal White Frame
Controls	Remote control	Remote control
Illumination	2 Strip LED 14 W with dimmable and tunable lightning	2 Strip LED 14 W with dimmable and tunable lightning
Filter Type	Aluminum Mesh Filter + Perimeter Aspiration	Aluminum Mesh Filter + Perimeter Aspiration
Duct Transition	6" Round Multidirectional	6" Round Multidirectional
Installation Type	Ducted or recirculating with kit	Ducted or recirculating with kit
Electrical	120 V - 60 Hz, 578 W	120 V - 60 Hz, 578 W
Kits Available	KIT0167875 - (Recirculating Kit) KIT0121468 - (White remote control) KIT0121469 - (Black remote control)	KIT0167875 - (Recirculating Kit) KIT0121468 - (White remote control) KIT0121469 - (Black remote control)

SPECS

Wall Mount Hoods






		
Model Name	Oristano Disegno Series	Catania Disegno Series
Model Numbers	EORX36SS (requires EAR634SS or EAR134S4) EORX48SS (requires EAR140S4)	ECTX36SS (requires ETR634SS or ETR134S1) ECTX48SS (requires ETR146SS)
Dimensions	36" W x 24" D x 30"H 48" W x 24" D x 30"H	136" W x 22" D x 34"H 48" W x 22" D x 34"H
Blower Type (sold separately)	600 CFM (4-speed) - 1200 CFM (4-speed)* **requires Arezzo insert	600 CFM (4-speed) - 1200 CFM (4-speed)* **requires Trento insert
CFM Reduction	No	No
Noise (sones)	7 Sones 8.5 Sones*	7 Sones 8.5 Sones*
Finish	Stainless Steel + Front and Lateral Rim Stainless Steel Mirror look + Decorative Bands & Bolts Stainless Steel Mirror Look	Stainless Steel + Front and Lateral Rim Stainless Steel Mirror look + Decorative Bands & Bolts Stainless Steel Mirror Look
Controls	Fully Retractable Rotating Knobs w/ Blue Backlight	Fully Retractable Rotating Knobs w/Blue Backlight
Illumination	2 LED, 6.5 W, 3000K, 540 lumen 4 LED, 6.5 W, 3000K, 540 lumen	2 LED, 6.5 W, 3000 K, 540 lumen
Installation	Elica Easy Mounting + Rear Outlet installation	Elica Easy Mounting + Rear Outlet installation
Filter Type	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter	Dishwasher-Safe, Professional Stainless Steel Angled Baffle Filter
Duct Transition	10" Round with Backdraft Damper (Top only)	10" Round with Backdraft Damper (Top only)
Kits Available	Compatible with Arezzo Kits	Compatible with Trento Kits

SPECS

Special Configurations



		
Model Name	Rise Techne Series	Capri Outdoor Series
Model Numbers	ERS630S1 ERS636S1	ECP136SS ECP148SS
Dimensions	30"W x 12 1/2"D x 14"H 36"W x 12 1/2"D x 14"H	36"W x 32"D x 18"H 48"W x 32"D x 18"H
Blower Type	600 CFM (3-speed + boost)	Internal or external 1200 CFM(4-speed)
CFM Reduction	Yes w/ Kit	No
Noise (sones)	6.8 Sones	8.5 Sones
Finish	Stainless Steel	Corrosion Resistant Grade Stainless Steel
Controls	External Electronic Rotating Disk + LCD	Fully Retractable Rotating Knobs w/ Blue Backlighting
Illumination	No Lightning	2 LED, 7.5 Watts LED light 4 LED, 7.5 Watts LED light <small>*Consumer Replaceable</small>
Installation Type	Ducted Installation only	Ducted Installation only
Filter Type	Dishwasher-Safe, Anodized Aluminum Mesh Filter + Perimeter Aspiration	Dishwasher-Safe, Professional Stainless Steel <small>4 w/ 36" & 6 w/48"</small>
Duct Transition	6" Round with Backdraft Damper (Side)	10" Round with Back Draft Damper (Top only)
Electrical	120 V - 60 Hz, 550 W	120V - 60 Hz, 913 W
Kits Available	KIT02748 - (CFM Reduction)	KIT0153054 - (External blower Kit) KIT0154387 - (Inline blower Kit) KIT0156655 - (Internal blower Kit) KIT0156637- KIT0156641 - (Duct Cover Kit 6") KIT0156645 - KIT0156649 - (Duct Cover Kit 12") KIT0153304- KIT0153305- (Spacer Kit 3" deep)

		
Model Name	NikolaTesla Switch Aircooking Series	
Model Numbers	ENS436BL	
Dimensions	36" W x 20 1/4"D x 8 1/4"H	
Blower Type	400 CFM (3-speed + boost)	
Noise (sones)	5.9 Sones*	
Cooking Zones	4 zones of 7.1" x 7.9"	
Heating Level	9 Levels + Booster	
Finish	Deep - Black Glass	
Controls	Slider touch control 3 speed + Booster ventilation	
Installation Type	Ducted or recirculating Self rimming or flush mounted	
Filter Specification	6 Layer Anodized Aluminum Mesh Filter	
Electrical	208 - 240 V - 60 Hz 440 Watts at 3.3 Amps 240 V - 7.8 kW at 32.5 Amps 208 V - 7.1 kW at 34.1 Amps	
Kits Available		














SPECS

Riserva Series - Undercounter Refrigeration












Model Name	Beverage & Wine Center FRENCH DOOR DUAL ZONE	Beverage Center SINGLE DOOR SINGLE ZONE	Beverage & Wine Center SINGLE DOOR DUAL ZONE	Wine Cellar SINGLE DOOR DUAL ZONE
Model Numbers	EBF52SS1	EBS51SS1	EBS52SS1	EWS52SS1
Dimensions	23 13/32" W x 22 13/32" D x 34 13/16" H	23 13/32" W x 23 5/8" D x 33 13/16" H	23 13/32" W x 23 5/8" x 33 13/16" H	23 13/32" W x 23 5/8" D x 33 13/16" H
Volume (Capacity)	4.8 cu ft (135L) Cooling Zone 1: > 60 Cans (12 oz) Cooling Zone 2: 21 Bottles of Wine (25 oz)	4.8 cu ft (135L) > 120 Cans (12 oz)	4.8 cu ft (135L) Cooling Zone 1: 72 Cans (12 oz) Cooling Zone 2: 14 Bottles of Wine (25 oz)	4.8 cu ft (135L) Cooling Zone 1: 16 Bottles of Wine (25 oz) Cooling Zone 2: 36 Bottles of Wine (25 oz)
Temperature Range	34 to 68°F	34 to 65°F	34 to 50°F 40 to 64° F	40 to 50°F 50 to 64° F
Refrigerant Type	R600a	R600a	R600a	R600a
Finish	Door: 304 Stainless Steel + UV Tempered Glass Cabinet/ Interior: Black Shelving: 3 Slide Out Tempered Glass + 6 Beechwood with metal front rim	Door: 304 Stainless Steel + UV Tempered Glass Cabinet/ Interior: Black Shelving: 3 Slide Out Tempered Glass Shelves with metal front trim	Door: 304 Stainless Steel + UV Tempered Glass Cabinet/ Interior: Black Shelving: 2 Slide Out Tempered Glass + 1 Beechwood with metal front rim	Door: 304 Stainless Steel + UV Tempered Glass Cabinet/ Interior: Black Shelving: 5 Beechwood with metal front rim
Illumination	3 Level White LED	3 Level White LED	3 Level White LED	3 Level White LED
Controls	Capacitive Touch Display with white numbers	Capacitive Touch Display with white numbers	Capacitive Touch Display with white numbers	Capacitive Touch Display with white numbers
Noise	39 dBA	39 dBA	39 dBA	39 dBA
Electrical	110-120 V / 60 Hz / 0.95 A Min. Circuit: 15 A	110-120 V / 60 Hz / 0.95 A Min. Circuit: 15 A	110-120 V / 60 Hz / 0.95 A Min. Circuit: 15 A	110-120 V / 60 Hz / 0.95 A Min. Circuit: 15 A
Features	Perfect Climate Technology Full extension Racks Anti Vibration Technology Eco Mode Quiet Operation Sabbath Mode	Perfect Climate Technology Full extension Racks Anti Vibration Technology Eco Mode Quiet Operation Sabbath Mode	Perfect Climate Technology Full extension Racks Anti Vibration Technology Eco Mode Quiet Operation Sabbath Mode	Perfect Climate Technology Full extension Racks Anti Vibration Technology Eco Mode Quiet Operation Sabbath Mode
Kits Available	KIT0175505 - (Pro Handle) L00114-1 (Carbon Filter)	KIT0175505 - (Pro Handle) L00114-1 (Carbon Filter)	KIT0175505 - (Pro Handle) L00114-1 (Carbon Filter)	KIT0175505 - (Pro Handle) L00114-1 (Carbon Filter)

Duct Cover Kit	
	KIT0156637
	KIT0156641
	KIT0156645
	KIT0156649
	KIT0182781
	KIT0182782
	KIT0182783
	KIT0182784
	KIT0182785
	KIT0182786
	KIT0182787
	KIT0182788
	KIT02158
	KIT02159
	KIT02160
	KIT02161
	KIT02164
	KIT02165
KIT02622	
KIT02623	
Island Chimney Extension Kit	
	KIT0100317
	KIT0145610
Chimney Extension Kit	
	KIT0100315
	KIT01609/1
	KIT0140998
	KIT01935
	KIT02762
KIT02785	
Wall Mount Chimney Extension Kit	
	KIT02784
High Ceiling Extension Kit	
	KIT0067590
	KIT01921

Recirculating Kit	
	CFC0038668
	CFC0141725AUL
	KIT0140997
	KIT0141924
	KIT0141925
	KIT0167875
	KIT02665
	KIT02721A
	KIT02766
	KIT02770
	KIT0102875
	KIT02178
	KIT02179
CFM Reduction Kit	
	KIT0175561
	KIT0185097
	KIT0185099
	KIT0185752
	KIT02748
Makeup Kit	
	KIT0148906A
	KIT0148914A
	KIT0148978A
	KIT0148981A

KITS

Deflector	
	DF01EA
	KIT0192763
Microhole Filter	
	GF04YB
Baffle Slot Filter Kit	
	GRI0131086A
	GRI0131087A
Backsplash Kit	
	KIT0142864
	KIT0142867
	KIT0142868
	KIT0142870
Hood Spacer	
	KIT0153304
	KIT0153305
Hood Liner	
	KIT02773
	KIT02773
	KIT02774
Backdraft Damper Kit	
	KIT0102873
	KIT02723
	KIT02724
Duct Transition	
	KIT02722
Heat Lamp	
	KIT0155106
	KIT0155107
	KIT0155107
	KIT0155111
Charcoal Filter	
	KIT02667
	KIT0192765

Internal Blower 1200 CFM	
	KIT0156655
External Blower 1200 CFM	
	KIT0153054
External Blower Shell	
	KIT0179547
Inline Blower 1200 CFM	
	KIT0154387
Inline Blower Shell	
	KIT0179549
Wall Mount Bracket	
	KIT0121394
Remote Control	
	KIT0121468
	KIT0121469
Recirculating Deflector	
	KIT0192759
	KIT0192761
Pro Handle Kit	
	KIT0175505

